

## Outdoor Premium Stainless Steel Dry Chemical Fire Extinguishers

**Dry Chemical Fire Extinguishers** extinguish a fire primarily by interrupting the chemical reaction of the fire triangle. Today's most widely used type of fire extinguisher is the multipurpose dry chemical that is effective on Class A, B, and C fires. This agent also works by creating a barrier between the oxygen element and the fuel element on Class A fires. Stainless Steel fire extinguishers are ideally suited for use outdoors or in corrosive environments such as heavy Industrial, waste & recycling facilities, oil & gas refineries, mining operations, farming and agriculture, coastal or marine operations and automotive interior & exterior applications.

### FEATURES

SUITABLE FOR CLASS A, B & C FIRES

STAINLESS STEEL CYLINDER AND HANDLE

BRASS VALVE

HIGH PERFORMANCE MULTIPURPOSE DRY

CHEMICAL POWDER

ISO9001 CERTIFIED

6 YEAR WARRANTY

BAGGED & BOXED INDIVIDUALLY



MODEL	PRODUCT DESCRIPTION	RATING	RANGE (FEET)	DISCHARGE TIME (SEC.)	PSI	HEIGHT (INCHES)	WIDTH (INCHES)	DIAMETER (INCHES)	WEIGHT (LBS)
N25AV-SS	2.5LB Multipurpose Dry Chemical Powder w/Vehicle Bracket	1-A:10-B.C.	8-10	9	195	14 1/8	6 1/8	3 1/2	6
N5AW340-SS	5LB Multipurpose Dry Chemical Powder w/Wall Bracket	3A:40-B.C.	8-10	14	195	17 1/4	9	4 3/8	10 1/4
NABC10-SS	10LB Multipurpose Dry Chemical Powder w/Wall Bracket	4-A:60-B.C.	8-15	22	195	20	9 1/4	5 1/2	18 3/8
NABC20-SS	20LB Multipurpose Dry Chemical Powder w/Wall Bracket	6-A:80-B.C.	8-15	23	195	23 1/4	10 5/8	1 1/8	33

## Carbon Dioxide Fire Extinguishers

**Carbon Dioxide Fire Extinguishers** extinguish fire by taking away the oxygen element of the fire triangle and also by removing the heat with a very cold discharge. Carbon dioxide can be used on Class B & C fires. They are ineffective on Class A fires.

### FEATURES

SUITABLE FOR USE ON CLASS B & C FIRES

BRASS VALVE CONSTRUCTION

STAINLESS STEEL HANDLES

HIGH PRESSURE TC & DOT ALUMINUM CYLINDER WITH

PHOSPHATE TREATED HIGH GLOSS POWDER COAT FINISH

ISO9001 CERTIFIED

5 YEAR WARRANTY

BOXED & BAGGED INDIVIDUALLY



MODEL	PRODUCT DESCRIPTION	RATING	RANGE (FEET)	DISCHARGE TIME (SEC.)	HEIGHT (INCHES)	WIDTH (INCHES)	DIAMETER (INCHES)	WEIGHT (LBS)
NCO25	5lb Carbon Dioxide c/w Wall Bracket ULC	2-B.C.	4 - 8	9	17 1/4	8 1/4	5 1/4	13 1/2
NCO210	10lb Carbon Dioxide c/w Wall Bracket ULC	10-B.C.	4 - 8	10	29 3/4	11 3/4	6 3/4	26 3/4
NCO215	15lb Carbon Dioxide c/w Wall Bracket ULC	10-B.C.	4 - 8	14	35 3/4	11 3/4	6 3/4	36 1/4
NCO220	20lb Carbon Dioxide c/w Wall Bracket ULC	20-B.C.	4 - 8	18	36 1/4	12 1/2	8	48