

Standpipe Rack Hose

SOFTFLEX rack hose is designed for quick and easy installation & annual refolding. Our hose is soft and flexible with a PU lining designed to stand up to multiple hydrostatic tests. Our couplings are all hydro tested after installation as per NFPA 1962 requirements to assure quality and performance. ULC and FM Approved.

FEATURES	State of the second
100% VIRGIN POLYESTER	
SINGLE JACKET, TWILL WEAVE	Anna 1
POLYURETHANE (PU) TUBE	E BARK
PACKAGE	
FOLDED, PACKED IN CARTON OF 2	
APPLICATION	
INTERIOR FIRE PROTECTION RACK HOSE IS	-
AN INTEGRAL PART OF THE BASE BUILDING	_
STANDPIPE FIRE PROTECTION SYSTEMS.	_



		MODEL	PRODUCT DESCRIPTION	DIAMETER	SERVICE PRESSURE	MINIMUM BURST PRESSURE
				(INCH/MM)	(PSI/BAR)	(PSI/BAR)
		RH-50	50' w/ Brass Couplings	1.5/40	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
\wedge		RH-75	75' w/ Brass Couplings	1.5/40	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
	UP	RH-100	100' w/ Brass Couplings	1.5/40	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
APPROVED	LISTED	RH-75CHR	75' w/ Polished Chrome Couplings	1.5/40	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
		RH-100CHR	100' w/ Polished Chrome Couplings	1.5/40	150/10,200/13, 220/14, 250/17	450/30, 600/39, 660/42, 750/51 FM,UL,ULC
		Standard leng	ths: 15m (50ft), 22.5m (75ft), 30m (100ft), also can be c	ustomized according to requirements	·

Fire Sprinkler Accessories

NOSREDNA HIGH IMPACT POLYCARBONATE

FOG NOZZLES are ULC Listed. They are manufactured to fit 1.5" fire hose couplings and adjustable position include Fog and Shut-off only. Suitable for Class A, B & C Fires. Maximum flow rate of 78 GPM at 100 PSI. Available in red or chrome molded finish.

NOSREDNA HIGH IMPACT POLYCARBONATE FOG AND STREAM NOZZLES are ULC Listed.

They are manufactured to fit 2.5" fire hose couplings and are adjustable positions include Fog, Stream and Shut-off only. Suitable for Class A, B & C Fires. Maximum flow rate of 150 GPM at 100 PSI. Available in red molded finish.





1575-C



2520-25CSA

	MODEL	PRODUCT DESCRIPTION	DIAMETER	Capacity	
		(INCH/MM)	(GPM) @100PSI		
(ULC)	1575	High Impact Polycarbonate Nozzle, Fog/Shut-Off	1.5/40	78	
	1575-C	High Impact Polycarbonate Nozzle - Chromed, Fog/Shut-Off	1.5/40	78	
	2520-25CSA	High Impact Polycarbonate Nozzle, Fog/Stream/Shut-Off	2.5/65	150	





Nitrile Rubber and Doube Jacket Fire Hose

NOSREDNA NITRILE RUBBER FIRE HOSE is excellent for water supply and municipal, industrial fire fighting. The polyester filament has a thin rib on the cover that increases performance and abrasion resistance. ULC Approved. Comes with aluminum couplings (CSA).

NOSREDNA DOUBLE JACKET EPDM RUBBER FIRE LINED HOSE is ideal for industrial fire fighting applications and Municipal Fire Department use. ULC and FM Approved. Comes with aluminum couplings.

NOSREDNA NITIRLE RUBBER FIRE HOSE

FEATURES	_			-0
NITRILE RUBBER		200		10 million
INCREASED ABRASION RSISTANCE				
ALUMINUM COUPLINGS	- Conclusion of	Concentrate & A	base of the second seco	
NOSREDNA DOUBLE JACKET EPDM RUBBER FIRE HOSE	() USTED	EX15978 No 0099772	m	(U) ustri
FEATURES	_	RUB-50		DJ-2100
DOUBLE JACKET, EPDM RUBBER				
CONSTRUCTION				
ALUMINUM COUPLINGS	LISTED			APPROVED LISTED

		MODEL	PRODUCT DESCRIPTION	DIAMETER	SERVICE PRESSURE	MINIMUM BURST PRESSURE
				(INCH/MM)	(PSI)	(PSI)
		RUB-25	25' w/ Aluminum Couplings	1.5/40	200	600
\bigtriangleup		RUB-50	50' w/ Aluminum Couplings	1.5/40	200	600
FM	(ULC)	RUB-100	100' w/ Aluminum Couplings	1.5/40	200	600
APPROVED	LISTED	DJ-225	25' w/ Aluminum Couplings	2.5/65	200	1200
		DJ-250	50' w/ Aluminum Couplings	2.5/65	200	1200
		DJ-2100	100' w/ Aluminum Couplings	2.5/65	200	1200


Fire Hose Reels



SADDLE-3030



HDR-18



HT-100

MODEL	PRODUCT DESCRIPTION	DIMENSIONS (INCHES)		CAPACITY	HOSE SIZE	
		WIDTH	DEPTH	HEIGHT	(FEET)	(INCHES)
SADDLE-3030	Saddle-Style Fire Hose Rack for 1 1/2" cotton, rubber-lined hose	16	6 1/4	10	100	1 1/2
SADDLE-3040	Saddle-Style Fire Hose Rack for 2 1/2" cotton, rubber-lined hose	16	9	10	100	2 1/2
HDR-18	Heavy Duty Hose Reel with 14 gauge steel wall bracket that swings 180 degrees.	23 1/2	6 1/4	18	100/75	1 1/2 Rack Hose
HDR-24	Heavy Duty Hose Reel with 14 gauge steel wall bracket that swings 180 degrees.	29	6 1/4	24	150/100	1 1/2 Rack Hose
HT-100	Hose Tray for Rubber or Industrial Hose	15	4	24	100/50	1 1/2 Rack Hose